



US009638367B2

(12) **United States Patent**
Iijima et al.

(10) **Patent No.:** **US 9,638,367 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **SATURATOR AND NATURAL GAS
REFORMING SYSTEM PROVIDED WITH
SAME**

(58) **Field of Classification Search**
CPC combination set(s) only.
See application file for complete search history.

(71) Applicant: **MITSUBISHI HEAVY INDUSTRIES,
LTD.**, Tokyo (JP)

(56) **References Cited**

(72) Inventors: **Masaki Iijima**, Tokyo (JP); **Masato
Matsuzawa**, Tokyo (JP)

U.S. PATENT DOCUMENTS

(73) Assignee: **MITSUBISHI HEAVY INDUSTRIES,
LTD.**, Tokyo (JP)

3,861,165 A * 1/1975 Hirano B01D 53/265
62/150
4,545,976 A * 10/1985 Osman C01B 3/382
252/373

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 101 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/437,076**

EP 0351711 A2 1/1990
EP 0766050 A2 4/1997

(Continued)

(22) PCT Filed: **Sep. 5, 2013**

OTHER PUBLICATIONS

(86) PCT No.: **PCT/JP2013/073924**

§ 371 (c)(1),

(2) Date: **Apr. 20, 2015**

Extended (Supplementary) European Search Report (EESR) dated
May 30, 2016, issued in counterpart European Patent Application
No. 13849858.9. (8 pages).

(Continued)

(87) PCT Pub. No.: **WO2014/065020**

PCT Pub. Date: **May 1, 2014**

Primary Examiner — Kaity Handal

(74) *Attorney, Agent, or Firm* — Westerman, Hattori,
Daniels & Adrian, LLP

(65) **Prior Publication Data**

US 2015/0276112 A1 Oct. 1, 2015

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

Oct. 26, 2012 (JP) 2012-236672

(51) **Int. Cl.**
B01J 19/24 (2006.01)
C01B 3/34 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **F16L 53/002** (2013.01); **B01J 19/24**
(2013.01); **C01B 3/34** (2013.01); **C01B 3/384**
(2013.01);

(Continued)

A saturator includes: a flow path inside of which a first fluid flows; a first heat exchange unit that causes heat exchange between the first fluid and a second fluid; a second heat exchange unit that causes heat exchange between a third fluid and the first fluid after the first fluid has passed through the first heat exchange unit; a humidifying unit that adds water to the first fluid upstream from the first heat exchange unit and the second heat exchange unit; and a conveyance path that conveys the third fluid after heat exchange from the second heat exchange unit to the upstream side of the first heat exchange unit and causes said third fluid to flow into the flow path as the first fluid.

3 Claims, 5 Drawing Sheets

